3-Pt Bale Handling

FRONTIER



Bale Unroller and 3-Pt Bale Spears
BU1060 • HS2001 • HS2002 • HS2003 • HS2004

FRONTIER.



Unroll round bales quickly and efficiently.

Haul and unroll round bales with a Frontier BU1060 Series Hydraulic Bale Unroller. This tough piece of equipment features:

- Compatible with Category 1 iMatch™ and Category 2 Quick-Hitch.
- A heavy-duty, welded, tubular frame provides strength and durability.

Get 4 feet (122 cm) or 5 feet (152 cm) wide round bales where you need them and unroll them quickly and efficiently so you can get on with the rest of your work. Performance. Durability. Ease of use. Value. Get them all with Frontier. Available exclusively from your local John Deere dealer.



Load up with 3-point bale spears from Frontier.

The Frontier range of 3-point bale spears are designed to suit a variety of needs or

preferences. Frontier offers spears that will handle round bales 4 feet (122 cm) or 5 feet (152 cm) wide and up to 6 feet (183 cm) in diameter.

All Frontier 3-point Bale Spears are built with welded components and high-tensile, heavy-gauge steel to deliver years of dependable service.











Specifications

Seeight 26.25 in, (66.7 cm) 24.75 in, (62.9 cm) 26.5 in, (67.3 c						
Seeight 26.25 in, (66.7 cm) 24.75 in, (62.9 cm) 26.5 in, (67.3 c	Model Number	BU1060	HS2001	HS2002	HS2003	HS2004
Modelsh	Dimensions					
Separating Sep	Height	26.25 in. (66.7 cm)	24.75 in. (62.9 cm)	26.5 in. (67.3 cm)	26.5 in. (67.3 cm)	26.5 in. (67.3 cm)
Neight Specialing 310 lb. (140.6 kg) 72 lb. ((32.7 kg) 138 lb. (62.6 kg) 178 lb. (80.7 kg) 255 lb. (115.7 kg)	Width	72.63 in. (184.5 cm)	37.5 in. (95.3 cm)	47.5 in. (120.7 cm)	60 in. (152.4 cm)	96 in. (243.8 cm)
Separating 310 lb. (140.6 kg) 72 lb. ((32.7 kg) 138 lb. (62.6 kg) 178 lb. (80.7 kg) 255 lb. (115.7 kg)	Length	61.38 in. (155.9 cm)	49.5 in. (125.7 cm)	51.5 in. (130.8 cm)	51.5 in. (130.8 cm)	51.5 in. (130.8 cm)
Add 12 12 15 15 15 15 15 15	Weight					
Cat. 1, Cat. 2 Cat. 1, Cat. 2 Cat. 2, Cat. 3 Cat. 2, Cat. 3 Cat. 2, Cat. 3	Operating	310 lb. (140.6 kg)	72 lb. ((32.7 kg)	138 lb. (62.6 kg)	178 lb. (80.7 kg)	255 lb. (115.7 kg)
Cat. 1, Cat. 2	Shipping	400 lb. (181.4 kg)	112 lb. (50.8 kg)	178 lb. (80.7 kg)	218 lb. (98.9 kg)	295 lb. (133.8 kg)
Test March Test	Hitch Type					
Yes Yes	Category	Cat. 1, Cat. 2	Cat. 1, Cat. 2	Cat. 2, Cat. 3	Cat. 2, Cat. 3	Cat. 2, Cat. 3
Sale Handling Pype	Cat. 1 iMatch	Yes	Yes	_	=	=
	Cat. 2 Quick-Hitch	Yes	Yes	Yes	Yes	Yes
Large round Large round Large round Large round Large square Large round	Cat. 3 Quick-Hitch	-	=	Yes	Yes	Yes
1	Bale Handling					
Capacity, lb. (kg) at 24 in. (60.96 cm) 2000 lb. (907.2 kg) 2200 lb. (997.9 kg) 3000 lb. (1360.8 kg) 3000 lb. (1360.8 kg) 4000 lb. (1814.4 kg) Capacity, lb. (kg) at 24 in. (60.96 cm) 2000 lb. (907.2 kg) 3 x3 in. (7.6 x 7.6 cm) 4 X 4 in. (10.2 X 10.2 cm)	Туре	Large round	Large round	Large round	Large square	Large round
Spears - Primary 4 x 4 in. (10.2 x 10.2 cm) 3 x 3 in. (7.6 x 7.6 cm) 4 X 4 in. (10.2 X 10.2 cm) 4 X 4 in. (Quantity	1	1	1	1	2
2 x 8 in. (5.1 x 20.3 cm) -	Capacity, lb. (kg) at 24 in. (60.96 cm)	2000 lb. (907.2 kg)	2200 lb. (997.9 kg)	3000 lb. (1360.8 kg)	3000 lb. (1360.8 kg)	4000 lb. (1814.4 kg)
Cylinder (optional)	Tube size	4 x 4 in. (10.2 x 10.2 cm)	3 x3 in. (7.6 x 7.6 cm)	4 X 4 in. (10.2 X 10.2 cm)	4 X 4 in. (10.2 X 10.2 cm)	4 X 4 in. (10.2 X 10.2 cm)
Quantity - 1 2 3 4 coation - Top Bottom Bottom Bottom size - 1.65 x 47 in. (4.2 x 119.4 cm) 1.65 x 47 in. (4.2 x 119.4 cm) 1.65 x 47 in. (4.2 x 119.4 cm) spears - Stabilizing - - - - - quantity - 2 - - - - coation - Bottom - - - - line 1.25 x 10 in. - - - -	Hydraulics		-	_	-	_
Top Bottom Bottom Bottom Bottom Bottom Bottom	Spears – Primary					
1.65 x 47 in. (4.2 x 119.4 cm) (4.2 x 119	Quantity	-	1	2	3	4
Coation Coat	Location	-	Тор	Bottom	Bottom	Bottom
Quantity - 2 - - - - cocation - Bottom - - - - 1.25 x 10 in. - - - - -	Size	-				
	Spears – Stabilizing					
1.25 x 10 in.	Quantity	-	2	_	-	_
	Location	-	Bottom	_	-	_
(3.2 x 25.4 cm)	Size	-	1.25 x 10 in. (3.2 x 25.4 cm)	_	-	