22 Series Mulch Finishers







MF2204 • MF2206 • MF2208

The quick, simple solution for proper seedbed preparation.

From tilling hard, layered soil to preparing existing food plots for reseeding, the 22 Series Mulch Finishers are designed for versatility and performance.

Choose from three affordable models: MF2204, MF2206, and MF2208. Designed for tractors from 30 to 100 horsepower (22-75 kw), the 22 Series Mulch Finishers come with 6, 8, or 12 disk blades. They provide excellent residue management and can help you achieve uniform tillage depth using any one of three distinct ground-engaging options.

Our standard 9-inch (22.9 cm) Sweeps lift the soil and spread it evenly for a smooth, level seedbed.

Our durable Chisel Spikes (optional) let you till and break up compacted soil in no time at all. And because the spikes pull through soil with less draft, you'll conserve fuel over each pass, reducing costs. Reversible tips give your spikes longer life.

The optional Turning Tips offer greater ground penetration through heavy residue, grass, or tough ground cover and break up soil compaction while turning over soil to bury residue.

The Frontier Mulch Finishers are sold and supported by John Deere, the most trusted name in farm, ranch and lawn equipment. To help you choose the right Frontier Mulch Finisher, talk to your local John Deere dealer, your exclusive source of Frontier Equipment.







9-inch Sweeps

Chisel Spikes (optional) Turning Tips (optional)

Details





As an additional option, attach the Rolling Basket (left) to the Frontier Mulch Finisher to till, condition, and level...all in a single pass! Designed to give you a smooth planting-ready seedbed each time. The efficiency saves time and money in your tilling operation while increasing planting productivity.

U.S.A. www.BuyFrontier.com Canada www.BuyFrontier.ca

Specifications

Model	MF2204	MF2206	MF2208
Tractor PTO hp (maximum)	30 - 50 hp (22.4 - 37.3 kW)	45 - 75 hp (33.6 - 55.9 kW)	60 - 100 hp (44.7 - 74.6 kW)
Hitch compatibility	iMatch™ compatible¹	iMatch™ compatible¹	iMatch [™] compatible ¹
Disking width	42 in. (107 cm)	60 in. (152 cm)	82 in. (208 cm)
S-Tine working width (with 9 in. sweeps)	51 in. (129.5 cm)	76 in. (193 cm)	96 in. (243.8 cm)
Unit length	53 in. (135 cm)	74 in. (188 cm)	74 in. (188 cm)
Unit height	35 in. (89 cm)	35 in. (89 cm)	35 in. (89 cm)
Machine weight	753 lbs (333 kg)	1,066 lbs (484 kg)	1,242 lbs (563 kg)
Number of blades	6	8	12
Blade diameter	16 in. (41 cm)	18 in. (46 cm)	18 in. (46 cm)
Blade thickness	0.118 in. (3 mm)	0.138 in. (3.5 mm)	0.138 in. (3.5 mm)
Blade spacing	8.25 in. (21 cm)	7.50 in. (19 cm)	7.50 in. (19 cm)
Blade type	Notched	Notched	Notched
Bearing hanger	.375 in. (1 cm) formed plate with reinforcement, (2) each .625 in. (1.6 cm) U-bolts per hanger	.375 in. (1 cm) formed plate with reinforcement, (2) each .625 in. (1.6 cm) U-bolts per hanger	.375 in. (1 cm) formed plate with reinforcement, (2) each .625 in. (1.6 cm) U-bolts per hanger
Bearing type	1 in. (2.5 cm) square sealed bearing	1 in. (2.5 cm) square sealed bearing	1 in. (2.5 cm) square sealed bearing
Gang axle	1 in. (2.5 cm) square	1 in. (2.5 cm) square	1 in. (2.5 cm) square
Gang adjustment	pinned adjustment	pinned adjustment	pinned adjustment
3-Point hitch type	Cat. 1	Cat. 1/2	Cat. 1/2
Number of S-tines	3	7	9
9-inch Sweep	3	7	9
1.75-inch Reversible chisel point (optional)	3	7	9
Right turning point (optional)	1	3	4
Left turning point (optional)	1	3	4

^{&#}x27;The iMatch Quick-Hitch does not work with all tractor series or with all implements. See your John Deere dealer to determine which tractors and implements are compatible with the iMatch





